



*“Taking Care of Business”*

toll free: 800-929-9473

## CATEGORY 3 PREMISE CABLE

### UTP - UNSHIELDED TWISTED PAIRS

### TYPE CMR NONPLENUM SIZES #24 & #22

**CONSTRUCTION:**

**CONDUCTOR** SOLID ANNEALED BARE COPPER.

**INSULATION** POLYVINYL CHLORIDE (PVC), COLOR CODED PER TELEPHONE COLOR CODE.

**CORE ASSEMBLY** INSULATED CONDUCTORS TWISTED INTO PAIRS OR VARYING TWIST LENGTHS TO MINIMIZE CROSSTALK AND CABLED TOGETHER.

**JACKET** POLYVINYL CHLORIDE (PVC).

Charlotte Wire Part#	Size AWG	Number of Pairs	Overall Diameter (in.)	Approx. Net Wt. (Lbs/Mft)
CW09601	24	2	.13"	10
CW09602	24	3	.15"	14
CW09603	24	4	.17"	18
CW09604	24	6	.19"	27
CW09605	24	8	.22"	36
CW09606	24	12	.25"	48
CW09607	24	25	.36"	98
CW09608	24	50	.50"	192
CW09609	24	75	.58"	285
CW09610	24	100	.67"	380
CW09611	24	200	.95"	730
CW09612	24	300	1.26"	1080
CW09613	22	2	.16"	14
CW09614	22	3	.17"	19
CW09615	22	4	.19"	27
CW09616	22	6	.23"	41
CW09617	22	12	.30"	72
CW09618	22	25	.42"	148
CW09619	22	50	.63"	290
CW09620	22	75	.72"	410
CW09621	22	100	.84"	550

**APPLICATION:**

Suitable for transmission in Local Area Networks up to 16MHz. Used for voice transmission, data transmission, and other premise installations.

**STANDARDS:**

NEC Article 800: Type CMR.