



“Taking Care of Business”

toll free: 800-929-9473

APPLIANCE, MOTOR LEAD & HOOKUP WIRE

TINNED COPPER, PVC INSULATION

UL 1007 80C 300VOLTS, UL 1569 105C 300VOLTS

CSA TR-64 90C 300VOLTS

CONSTRUCTION:

CONDUCTOR SOFT DRAWN TINNED COPPER.

INSULATION POLYVINYLCHLORIDE (PVC)

Charlotte Wire Part#	Size AWG	Stranding Strand Number X Size	Insulation Thickness (in.)	Overall Diameter (in.)	Approx. Net Weight (Lbs/Mft.)
CW04156	24	Solid	.015"	.052"	2
CW04157	22	Solid	.015"	.062"	3
CW04158	20	Solid	.015"	.068"	5
CW04159	18	Solid	.015"	.073"	7
CW04160	16	Solid	.015"	.090"	10
CW04161	26	7x 34awg	.015"	.051"	2
CW04162	24	7x 32awg	.015"	.057"	2
CW04163	22	7x 30awg	.015"	.062"	3
CW04164	20	10x 30awg	.015"	.070"	5
CW04165	18	16x 30awg	.015"	.080"	7
CW04166	16	26x 30awg	.015"	.095"	10
CW04167	14	41x 30awg	.015"	.110"	18
CW04168	12	65x 30awg	.015"	.130"	24
CW04169	10	105x 30awg	.015"	.150"	37

APPLICATION:

Suitable for use in electronic circuits, control wiring, and internal appliance wiring.

STANDARDS:

UL AWM Style 1007 80C 300V (sizes 26-16awg).

UL AWM Style 1569 105C 300V (sizes 26-10awg).

CSA TR-64 90C 300V