

## MESSENGER CABLES

### EXTRA HIGH STRENGTH GALVANIZED MESSENGER (EHSGSM)

Part Number	Size	Stranding	Breaking Strength	Weight (Lbs/Mft)
3/16EHSGSM	3/16"	7stranded	3990lbs	73
1/4EHSGSM	1/4"	7stranded	6650lbs	121
5/16EHSGSM	5/16"	7stranded	11200lbs	205
3/8EHSGSM	3/8"	7stranded	15400lbs	273
7/16EHSGSM	7/16"	7stranded	20800lbs	399
1/2EHSGSM	1/2"	7stranded	26900lbs	517
9/16EHSGSM	9/16"	7stranded	35000lbs	671
5/8EHSGSM	5/8"	7stranded	42400lbs	813
3/4EHSGSM	3/4"	19stranded	58300lbs	1155
1EHSGSM	1"	19stranded	104500lbs	2073

### TYPE 302 STAINLESS STEEL MESSENGER (302SSM)

Part Number	Size	Stranding	Breaking Strength	Weight (Lbs/Mft)
1/4302SSM	1/4"	7stranded	8500lbs	135
9/32302SSM	9/32"	7stranded	10700lbs	170
5/16302SSM	5/16"	7stranded	13200lbs	212
3/8302SSM	3/8"	7stranded	18000lbs	282
7/16302SSM	7/16"	7stranded	26000lbs	416
1/2302SSM	1/2"	7stranded	33700lbs	535

### EXTRA HIGH STRENGTH COPPER CLAD STEEL 30% CONDUCTIVITY (EHSCCS30%)

Part Number	Size	Stranding	Breaking Strength	Weight (Lbs/Mft)
1/4EHSCCS30%	O.D. .242" (approx. 1/4")	7 No. 12	5670lbs	129
5/16EHSCCS30%	O.D. .306" (approx. 5/16")	7 No. 10	8921lbs	206
3/8EHSCCS30%	O.D. .386" (approx. 3/8")	7 No. 8	13476lbs	328
7/16EHSCCS30%	O.D. .433" (approx. 7/16")	7 No. 7	16393lbs	409
1/2EHSCCS30%	O.D. .486" (approx. 1/2")	7 No. 6	19845lbs	521
9/16 EHSCCS30%	O.D. .546" (approx. 9/16")	7 No. 5	23909lbs	650
5/8EHSCCS30%	O.D. .613" (approx. 5/8")	7 No. 4	28552lbs	819

### ALUMINUM CLAD STEEL (ACS)

Part Number	Size	Stranding	Breaking Strength	Weight (Lbs/Mft)
1/4ACS	O.D. .242" (approx. 1/4")	7 No. 12	6301lbs	104
5/16ACS	O.D. .306" (approx. 5/16")	7 No. 10	10020lbs	165
3/8ACS	O.D. .385" (approx. 3/8")	7 No. 8	15930lbs	262
7/16ACS	O.D. .433" (approx. 7/16")	7 No. 7	19060lbs	330
1/2ACS	O.D. .486" (approx. 1/2")	7 No. 6	22730lbs	417
9/16ACS	O.D. .546" (approx. 9/16")	7 No. 5	27030lbs	525