# **Ferotec Friction Ltd**

# **D3714 Safety Data Sheet**

### IDENTIFICATION OF THE SUBSTANCE/PREPARATION OF THE COMPANY

COMMON USES:

1.

S: Brakes/Clutch Lining

SUPPLIER:

Ferotec Friction Ltd Unit C Greenfield Business Park Bagillt Rd Holywell Flintshire CH8 7HJ United Kingdom Tel: +44 1352 710360 Fax: +44 1352 719368 Emergency Tel: + 441352 710360

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

This product contains a number of ingredients, all of which have become sealed in a synthetic rubber/resin binder resulting in a low probability of dust/fibre release.

Chemical Name	CAS No	Concentration (%)`	OEL	Exposure limit	Risk Phrases
Mineral Fibres (E-glass continuous filament fibre and rock wool fibre)	65997-17-3	< 27	2 fibres/ml, 5mg/m³dust	8 hour TWA	R38, R40
Barium sulphate	7727-43-7	< 9	Respirable 4 mg/m <sup>3</sup> Total inhalable 10 mg/m <sup>3</sup>	8 hour TWA	
Synthetic rubber	67254-76-6	< 2	o.6 mg/m <sup>3</sup> fume 6 mg/m <sup>3</sup> dust	8 hour TWA	

### 3. HAZARD IDENTIFICATION

Exposure to dust created by handling this product should be kept a low as reasonably practicable and limits as above are observed. Handling of this product may cause skin irritation. No health risks have so far been known in cases where this product has been handled and processed properly.

Specific Hazards The mineral fibres have been classified by the EU as Carc.Cat.3 (substances which cause concern for man owing to possible carcinogenic effect) and as an irritant to skin. High dust levels may irritate the throat and eyes. FIRST AID MEASURES 4. Inhalation Avoid breathing dust. In the event of excessive inhalation of dust, remove the individual to fresh air. Obtain medical advice. Clean skin with soap and water. Obtain medical advice if irritation persists. Skin Contact **Eye Contact** Irrigate with clean water for at least 15 minutes. Obtain medical advice if irritation persists, Ingestion It is not normally considered that the product will be ingested, but if small quantities are ingested, seek medical advice. FIRE-FIGHTING MEASURES 5. **Extinguishing Media** Any standard extinguishing media may be used. Fire fighters, and others exposed, wear self-contained breathing apparatus. **Protective Equipment Exposure Hazards** When heated to very high temperatures, may give off smoke and decomposition products which may contain toxic compounds. ACCIDENTAL RELEASE MEASURES 6. Personal Precautions Use personal protective equipment as recommended in section 8. Avoid breathing dust. **Environmental Precautions** No special precaution required Methods for Cleaning up Remove any dust generated by vacuum or wet cloth. Issue 3 May 11 Page 1 of 3

Ferotec Friction Ltd Unit C Greenfield Business Park, Bagillt Rd, Holywell, Flintshire CH8 7HJ, United Kingdom Tel: +44 1352 710360 Fax: +44 1352 719368 E-mail: ffsales@ferotecfriction.co.uk Website: www.ferotecfriction.com

# **Ferotec Friction Ltd**

# **D3714 Safety Data Sheet**

#### 7. HANDLING AND STORAGE

Handling Excessive handling may generate dust. Use adequate ventilation to keep dust concentration below stipulated standard. **Storage Conditions** Prevent exposure to temperatures above 100°C. EXPOSURE CONTROLS/PERSONAL PROTECTION 8. Use local exhaust ventilation to maintain airborne dust levels to below established **Engineering measures** exposure standard. Personal Protection **Respiratory Protection** Wear suitable protection if exposure limits are exceeded. Hand Protection Wear impervious gloves.; use suitable barrier creams and maintain good hygiene standards

Wear overalls of close weave material

Skin Protection

Eye Protection

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Black solid	Colour	Black		
pH-value	Not applicable	Melting point/range	Not applicable		
<b>Explosive properties</b>	As supplied, does not present an explosion hazard. however, dust produced from grinding operations				
	presents an explosion hazard.				
Density	1.80g/cm <sup>3</sup>	Autoflammability	> 350°C		
Flammability	Does not support combustion but will burn at elevated temperatures. Will burn when finely divided.				
Odour	Characteristic friction material odou	r Boiling point/range	Not applicable		
Flash point	Not applicable	Vapour pressure	Not applicable		
Solubility in water	Not applicable	Viscosity	Not applicable		

### 10. STABILITY AND REACTIVITY

Stability Conditions to avoid Materials to avoid Hazardous decomposition products Hazardous Reactions

TOXICOLOGICAL INFORMATION

Short Term Effects Inhalation Ingestion Skin Contact Eye Contact

Chronic Effects Inhalation

11.

Ingestion Skin Contact Eye Contact Carcinogenicity Stable Prolonged exposure to elevated temperatures >300°C Not applicable  $CO, CO_2, NO_x, SO_x$ , phenol, formaldehyde and cyanides None - relatively inert

Wear safety glasses when machining or abrading the product.

May cause irritation to upper respiratory tract Not established May cause temporary irritation May cause irritation

The glass fibre present in this product is not classified as respirable (*fibres with diameters <3.0µm that are capable of entering the respiratory system*). Assessment of toxicity of man-made mineral fibres has identified the fact that fibres which cannot enter the respiratory system will not be a factor for the induction of respiratory diseases.

Not established

Not established Not established

The International Agency for Research on Cancer designated glass fibre a Group 3 "not classifiable as to human carcinogenicity". Rockwool fibres are classified by the EU as Carc.Cat.3 (substances which cause concern for man owing to possible carcinogenic effect). See below:

Mineral Fibres

#### 11.1 Coarse fibres

Coarse fibres can cause itching of the skin, foreign body reaction in the upper respiratory system (mucous membranes) and in the eyes. The itching and possible inflammation are a mechanical reaction to the coarse fibres (of more than about  $5\mu$ m in diameter) and are not damaging in the way chemical irritants may be. They generally abate within a short time after the end of the exposure. When products are handled continually, the skin itching generally diminishes. 11.2 Respirable fibres

### Animal studies

Lifetime inhalation studies of rats exposed to high levels of stone wool fibres have not shown any excess of lung tumours. However, they did produce evidence of fibrosis

Issue 3 May 11

Page 2 of 3

Ferotec Friction Ltd Unit C Greenfield Business Park, Bagillt Rd, Holywell, Flintshire CH8 7HJ, United Kingdom Tel: +44 1352 710360 Fax: +44 1352 719368 E-mail: ffsales@ferotecfriction.co.uk Website: www.ferotecfriction.com

# **Ferotec Friction Ltd**

# **D3714 Safety Data Sheet**

(scar tissue) at the higher exposure levels. The fibrosis occurred late and was at a low level. Studies using non-physiological routes of administration (implantation or injection) and high does of fibres have shown an excess of tumours. Experiences in humans (Epidemiological Studies)

Large morbidity and mortality studies of both European and North American mineral wool manufacturing workers have been conducted.

the studies have found no significant evidence of non-malignant lung disease (e.g. fibrosis). The studies have not established a casual relationship between exposure to stone wool and malignant diseases (lung cancer or mesothelioma). In the latest follow-up in Europe, there was some excess of lung cancer. However, much of the excess was observed in one production plant, where workers had been exposed to asbestos and polycyclic hydrocarbons. For the remaining plants, there was little evidence of an association of stone wool production and any excess of lung cancer. To

establish reasons for the unexplained excess, a case-control study is being conducted.

### 12. ECOLOGICAL INFORMATION

Bioaccumulation Mobility Ecotoxic effects Biodegradation

## DISPOSAL CONSIDERATION

Product

13.

**Contaminated Packaging** 

Not inherently biodegradable

Seal all dust created by abrading in impervious bags and dispose to a suitable licensed landfill site. Remove all packaging for recovery or incinerate/landfill

#### 14. TRANSPORT INFORMATION

Not classified as dangerous for conveyance. use any container of suitable size and length.

Not established

Not established

Not established

### 15. REGULATORY INFORMATION

EEC Classification The product contains Mineral Fibres (Machine made vitreous (silicate) fibres). Danger symbol Xn. Harmful Irritating to skin (R38) **Risk Phases** Possible risks of irreversible effects (R40) Safety Phrases Wear suitable protective clothing and gloves (S<sub>3</sub>6/<sub>37</sub>) Refer to Health & Safety at Work Act 1974 Control of Substances hazardous to Health (COSHH) Regulations 1994 Please note This Safety Data Sheet does not constitute the user's own assessment of workplace risk as required by other health and safety legislation. ADDITIONAL INFORMATION 16. Further Information Health and Safety Executive Guidance Note EH40/2000- Occupational Exposure Limits 2000 Health and Safety Executive Guidance Note EH46- Man-Made Mineral Fibres Health and Safety Executive Guidance Note MDHS14 - General Methods for the Gravimetric Determination of Respirable and Total Inhalable Dust Health and Safety Executive Guidance Note MDHS59 - Man-Made Mineral Fibre

This information is based on our present knowledge and is accurate at the date of issue, to the best knowledge of Ferotec Friction Ltd. However, it shall not constitute a guarantee for any specific product featured and shall not establish a legally contractual relationship and condition or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with handling, storage , use or disposal of the product.

For any additional information, contact Ferotec Friction Ltd.

Issue 3 May 11

Page 3 of 3

Ferotec Friction Ltd Unit C Greenfield Business Park, Bagillt Rd, Holywell, Flintshire CH8 7HJ, United Kingdom Tel: +44 1352 710360 Fax: +44 1352 719368 E-mail: ffsales@ferotecfriction.co.uk Website: www.ferotecfriction.com