

STEEL-CASTER™

FISHER®



THE ALL-NEW STEEL-CASTER™ 0.35 CU YD STAINLESS STEEL HOPPER SPREADER

There's no better way to apply the finishing touch to sidewalks, paths and small driveways than with the new FISHER® STEEL-CASTER™ stainless steel hopper spreader. With a 0.35 cu yd capacity, it's designed to be the right size for UTVs and compact trucks while retaining many of the same features of larger STEEL-CASTER hopper spreaders.

Photo may be shown with optional accessories.

FISHERPLOW.COM

FISHER® STEEL-CASTER™

0.35 CU YD STAINLESS STEEL HOPPER SPREADER



Photo may be shown with optional accessories.

ADVANTAGES

- Purpose-built for UTVs and compact trucks
- Convenient flip-up chute
- 11½"-wide pintle chain conveyor system
- Dual variable-speed control

AVAILABLE ACCESSORIES

- 0.25 cu yd Extension Collars
- Spill Guard Kit
- LED Work Light Kit
- LED Strobe Light Kit
- Central Point Grease Kit
- Vibrator Kit
- Inverted V Kit
- License Plate Kit
- Ratchet Tie-Down Kit
- Truck Upfit Kit
- UTV Spreader Control Shield

HOPPER CONSTRUCTION

- The low-maintenance, stainless steel, riveted construction provides longevity and protection against stress.

MATERIAL DELIVERY

- Features a 11½"-wide pintle chain conveyor system that moves material consistently and smoothly to prevent bridging.

DUAL VARIABLE-SPEED CONTROL

- Enhanced dual variable-speed control allows you to precisely match material delivery and spread patterns to conditions.

FLIP-UP CHUTE

- Provides convenient access to the hitch and easy clean-out.

EXTENSION COLLAR (ACCESSORY)

- Designed for UTVs and compact trucks that can handle the extra weight, a 0.25 cu yd extension collar is available as an accessory to increase material capacity.

ACCESSORY INTEGRATION

- Conveniently connect accessories directly into the hub mounted in the back of the hopper. Accessories automatically integrate with the hopper control without having to run additional wires from the front of the vehicle.

Body Side Length	Capacity	Hopper Construction	Hopper Dimensions	Overall Dimensions	Min. Bed Length Required	Approx. Weight (Empty) Dual 12V DC Sealed Motors	Conveyor Width	Spinner Size	Spreading Width	Material	Vehicle Application
30" (0.76 m)	0.35 cu yd (0.27 cu m)	16 ga SS (1.5 mm SS)	30" x 38" x 26" (76.20 cm x 96.52 cm x 66.04 cm)	57" x 38" x 46" (144.78 cm x 96.52 cm x 116.84 cm)	30" (76.20 cm)	235 lb (106.59 kg)	11½" (29.21 cm)	12" (30.48 cm)	Up to 30 ft (Up to 9.14 m)	Salt, Sand, Salt/Sand Mix	UTVs and Compact Trucks



Fisher Engineering | 50 Gordon Drive | Rockland, Maine 04841

fisherplows.com |    



Fisher Engineering reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Fisher Engineering or the vehicle manufacturer may require or recommend optional equipment for spreaders. Do not exceed vehicle weight ratings with a spreader. This product is manufactured under the following patents US: 7,400,058; 7,737,576; other patents pending. Fisher Engineering offers a limited warranty on all spreaders and accessories. See separately printed page for this important information. The following are registered (®) or unregistered (™) trademarks of Douglas Dynamics, LLC: FISHER®, STEEL-CASTER™.