

**STEEL-CASTER™**

**FISHER®**



## THE ALL-NEW STEEL-CASTER™ 0.7 CU YD STAINLESS STEEL HOPPER SPREADER

Make easy work of snow and ice with a hopper spreader that's purpose-built for half-ton and light-duty trucks. Designed with a 0.7 cu yd capacity, the all-new STEEL-CASTER™ stainless steel hopper spreader has all the power and performance of larger FISHER® STEEL-CASTER hopper spreaders, but in a more compact size to better accommodate your smaller spaces and jobs.

*Photo may be shown with optional accessories.*

**FISHERPLOW.COM**

# FISHER® STEEL-CASTER™

## 0.7 CU YD STAINLESS STEEL HOPPER SPREADER



Photo may be shown with optional accessories.

### ADVANTAGES

- Purpose-built for half-ton and light-duty trucks
- Convenient flip-up chute
- 15½"-wide pintle chain conveyor system
- Dual variable-speed control

### AVAILABLE ACCESSORIES

- 0.5 cu yd Extension Collars
- 50-Gallon Pre-Wet and Direct Liquid Application Kit
- Spill Guard Kit
- LED Work Light Kit
- LED Strobe Light Kit
- Central Point Grease Kit
- Vibrator Kit
- Inverted V Kit
- Ratchet Tie-Down Kit

### HOPPER CONSTRUCTION

- The low-maintenance, stainless steel, riveted construction provides longevity and protection against stress.

### MATERIAL DELIVERY

- Features a 15½"-wide pintle chain conveyor system that moves material consistently and smoothly to prevent bridging.

### DUAL VARIABLE-SPEED CONTROL

- Enhanced dual variable-speed control allows you to precisely match material delivery and spread patterns to conditions.

### FLIP-UP CHUTE

- Provides convenient access to the hitch and easy clean-out.

### 50-GALLON PRE-WET & DIRECT LIQUID APPLICATION KIT (ACCESSORY)

- Provides operators the ability to pre-wet materials or spray brine directly onto the driving surface for anti-icing applications.
- The accessory kit includes two 25-gallon pre-wet tanks, a pump and a spray kit.

### ACCESSORY INTEGRATION

- Conveniently connect accessories directly into the hub mounted in the back of the hopper. Accessories automatically integrate with the hopper control without having to run additional wires from the front of the truck.

Body Side Length	Capacity	Hopper Construction	Hopper Dimensions	Overall Dimensions	Min. Bed Length Required	Approx. Weight (Empty) Dual 12V DC Sealed Motors	Conveyor Width	Spinner Size	Spreading Width	Material	Vehicle Application
54" (1.37 m)	0.7 cu yd (0.54 cu m)	16 ga SS (1.5 mm SS)	54" x 43" x 28" (137.16 cm x 109.22 cm x 71.12 cm)	81" x 43" x 46" (205.74 cm x 109.22 cm x 116.84 cm)	44" (111.76 cm)	420 lb (190.51 kg)	15½" (39.37 cm)	12" (30.48 cm)	Up to 30 ft (Up to 9.14 m)	Salt, Sand, Salt/Sand Mix	½-Ton & Light-Duty Pickup Trucks



Fisher Engineering | 50 Gordon Drive | Rockland, Maine 04841

fisherplows.com |    



Fisher Engineering reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Fisher Engineering or the vehicle manufacturer may require or recommend optional equipment for spreaders. Do not exceed vehicle weight ratings with a spreader. This product is manufactured under the following patents US: 7,400,058; 7,737,576; other patents pending. Fisher Engineering offers a limited warranty on all spreaders and accessories. See separately printed page for this important information. The following are registered (®) or unregistered (™) trademarks of Douglas Dynamics, LLC: FISHER®, STEEL-CASTER™.